



### Main

|                           |         |
|---------------------------|---------|
| Range                     | C-Bus   |
| Product brand             | Clipsal |
| Product or component type | Relay   |
| Device application        | Control |

### Complementary

|                           |              |
|---------------------------|--------------|
| [Us] rated supply voltage | 15...36 V DC |
| Network type              | AC/DC        |
| Local signalling          | LED          |
| Width                     | 36 mm        |
| Height                    | 93 mm        |
| Depth                     | 63 mm        |

### Environment

|                         |      |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

### Packing Units

|                  |            |
|------------------|------------|
| Package 1 Weight | 206.000 g  |
| Package 1 Height | 77.000 mm  |
| Package 1 width  | 110.000 mm |
| Package 1 Length | 155.000 mm |

### Offer Sustainability

|                        |  |
|------------------------|--|
| RECh Regulation        | <a href="#">REACH Declaration</a>                |
| RECh free of SVHC      | Yes  |
| EU RoHS Directive      | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free | Yes  |
| Mercury free           | Yes  |

|                            |   |
|----------------------------|---|
| RoHS exemption information | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |