



Invicta 24P Chassis-160A ISO-STD-WH

JVC2400S16TW

Architecture

Fixing mode	surface-mounting
Number of poles of the main switch	3

Functions

Overvoltage protection	no
------------------------	----

Main electrical features

Rated operational voltage U_e	415 V
Nominal voltage	400 V
Frequency	50/60 Hz

Electric current

Rated current	160 A
---------------	-------

Cover, door

Type of door closing	with keylock
Interlockable	no
Number of keylock of the door	1
Transparent cover or door	no

Materials

Colour	light grey
RAL colour	RAL 7035 - Light grey
Material	Steel

Dimensions

Insertion depth	117 mm
Depth of installed product	135 mm
Internal depth	115 mm
Height of installed product	800 mm
Width of installed product	480 mm
Thickness of sidewall material	1,2 mm

Connection

Number of accessible phases	24
-----------------------------	----

Accessories included

Mounting plate included	no
With lock	yes

Equipment

Quantity of rails	1
Can be accessorized	yes
With bell transformer	no
Extension possible	yes
With socket	no

Safety

IK protection code against mechanical impacts	05
Protection index IP	IP30
Protection class	isol.class I
Glow wire test	according to AS/NZS 61439-1
Type of protection devices	Miniature- / earth leakage circuit breaker