



SPD 4P TNS/TT 8 kA

SPB408D

Controls and indicators

Indicator lamp	Optic
----------------	-------

Main electrical features

Rated operational voltage Ue	240 / 415 V
Frequency	50/60 Hz
Nominal discharge current (In) 8/20 μ s, IEC 61643)L-N(PEN)/ N-PE	2 / 20 kA

Voltage

Maximum continuous operating voltage Uc	275 V
Voltage protection level Up according to IEC61643-1	0,9 kV
Voltage protection level Up L-PE/N-PE according to IEC61643-11	1,5 kV
Voltage level Up L-N/PEN IEC61643-11	0,9 kV
Maximum continuous operating voltage Uc_AC IEC61643	275 V

Electric current

Calibration of the protection upstream	125 A
Max discharge I _{max} (8/20 μ s, IEC 61643)	8 kA
Max discharge (I _{max}) L-N(PEN)/ N-PE	8 / 40 kA

Electrical specifications

Short-circuit breaking capacity (I _{sc} cr)	25 kA
--	-------

Network configuration

Network type	TT/TN-S
--------------	---------

Dimensions

Depth of installed product	58,2 mm
Height of installed product	89,8 mm
Width of installed product	71,2 mm

Installation, mounting

Tightening torque	3
-------------------	---

Connection

Connection cross-section of input and output with screws, for massive conductors	1,5 / 35 mm ²
Connection cross section of access and exit with screws, for flexible conductor	1,5 / 25 mm ²

Equipment

With remote signalling contact	no
--------------------------------	----

Standards

Approvals	KEMA, NF
Test class IEC61643-11 / VDE0675-6-11	T2
European directive WEEE	concerned

Use conditions

Operating temperature	-40 80 °C
-----------------------	-----------
