



SKYLUX

SKYLUX200W-G2

SAP CODE: 2002091



Photometric Diagram



Unit: cd
 - C0/180 113.4deg
 - C90/270 113.3deg

200W, 0-10V Dimming,
Wide voltage range,
Power switchable LED
High efficacy Highbay

A versatile, cost effective LED
Highbay for lighting large
industrial spaces

KEY INFORMATION

| | |
|-----------------|---------------------------|
| Lumen Output | 19000/22000/25000/30000lm |
| Input Power | 130/150/170/200W |
| Dimming Options | 0-10V Dimming |
| Trim Colour | BLACK |
| Warranty | 5yr |
| IP Rating | IP65 |
| IK Rating | IK08 |

PHOTOMETRIC

| | |
|------------|---------|
| Efficacy | 150lm/W |
| LED | SMD |
| CCT | 5000K |
| CRI | 80 |
| Beam Angle | 110° |

ELECTRICAL

| | |
|-----------------------------|-------------------|
| Driver | Integral |
| Supply Input | 100-277V, 50/60Hz |
| Driver Output Voltage | 200VDC |
| Power Factor | >0.9 |
| LED Input Current (nominal) | 700-1000mA |
| Useful life @Ta25° (L70) | 50,000hr |

CONSTRUCTION

| | |
|---------------------------|------------------------|
| Housing | Aluminium ADC12 |
| Optics | Polycarbonate Diffuser |
| Adjustable Angle | N/A |
| Fixings/Hardware | N/A |
| Connection Type | 1.5m Flex & Plug |
| Total Weight | 4kg |
| Dimensions | Ø340 x 197mm |
| Operating Ambient Temp. | -35 to 50°C |
| Electrical Classification | Class 1 |