

# DATA SHEET

## CONDUIT FULL SADDLE

**Attributes:**

- Zinc plated or hot dip galvanized for strength
- Varied hole size for fixing
- Custom shape for ease of attachment
- High quality construction for extra durability



Item Code	Nominal Diameter (mm)	Gauge (mm)	Hole (mm)	Centres (mm)	Length (mm)	Width (mm)	Height (mm)	Surface Treatment
KIMCFS12	12.7	0.7	5	28	40	13	14	Zinc plated
KIMCFS16	16	0.7	5	32	45	13	18	Zinc plated
KIMCFS20	20	0.9	5	39	50	16	23	Zinc Plated
KIMCFS25	25	0.9	5	48	62	19	28	Zinc plated
KIMCFS32	32	1.2	6	63	79	25	35	Zinc plated
KIMCFS40	40	1.2	6	71	87	25	44	Zinc plated
KIMCFS50	50	1.2	6	92	108	25	53	Zinc plated
KIMCFS12HDG	12.7	0.7	5	28	40	13	14	Zinc plated
KIMCFS16HDG	16	0.7	5	32	45	13	18	Hot dip Galvanized
KIMCFS20HDG	20	0.9	5	39	50	16	23	Hot dip Galvanized
KIMCFS25HDG	25	0.9	5	48	62	19	28	Hot dip Galvanized
KIMCFS32HDG	32	1.2	6	63	79	25	35	Hot dip Galvanized
KIMCFS40HDG	40	1.2	6	71	87	25	44	Hot dip Galvanized
KIMCFS50HDG	50	1.2	6	92	108	25	53	Hot dip Galvanized
KIMCFS63HDG	63	1.6	7	107	130	39	66	Hot dip Galvanized