

Conix Downlight

Featuring a low glare design for visual comfort, as well as a simple and stylish form, the Conix downlight is the perfect solution for both residential and commercial applications. The Colour Select option provides flexibility to create the right ambience for any environment.

- Low glare recessed diffused 60 degree lens
- IP44 ingress protection (front only)
- Colour Select - 3000K, 4000K, and 6500K



COLOUR SELECT



80

CRI



IP44

Ingress Protection Rating



IK03

Impact Rating



19

UGR Design



5SDCM

MacAdam Steps



0 to 40

Operating Temperature



Phase

Dimming



50,000hrs (L70/B10) @ 40°C

Lifetime



3 Years

Warranty




Symmetric

Beam Distribution


CODE	LAMP POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	LUMINAIRE COLOUR
CNX63/4/65B	6.5W	650lm	100lm/W	4000K	L110 x W110 x H85 mm	Black
		590lm		3000K		
		600lm		6500K		
CNX63/4/65W	6.5W	770lm	115lm/W	4000K	L110 x W110 x H85 mm	White
		740lm		3000K		
		750lm		6500K		

Line Drawings





CNX63/4/65W




CNX63/4/65W



CNX63/4/65B



CNX63/4/65B



CNX63/4/65B