# **Product datasheet**

Specifications



# T2S socket-outlet subassembly 3-Ph IEC - Wallbox spare part

EVP1HSM43

### Main

Range	EVlink
Product Or Component Type	Socket-outlet
Socket-Outlet Type	T2 with shutter
Poles Description	3P + N
[Us] Rated Supply Voltage	380415 V AC 50/60 Hz
Maximum Supply Current	32 A
Earthing System	Compatible TT Compatible IT with additional isolation transformer on the power supply Compatible TN
Nominal Output Power	22 W 32 A
Range Compatibility	EVlink EVlink Wallbox EVH2 charging station

### Complementary

Material	Plastic
Product Certifications	CE
Height	110 mm
Width	110 mm
Depth	90 mm

## Environment

Ip Degree Of Protection	IP54 conforming to IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ambient Air Temperature For Operation	-3050 °C
Ambient Air Temperature For Storage	-4080 °C
Relative Humidity	595 %

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15 cm
Package 1 Width	15 cm
Package 1 Length	30 cm
Package 1 Weight	654 g

Unit Type Of Package 2	S01
Number Of Units In Package 2	1
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	879 g

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information