

Product datasheet

Specifications



EVlink PKG T2 SOCKET GREEN TRANSPARENT EV SPARE PART

EVP1PSS2

Main

Range	EVlink
Product Or Component Type	Socket-outlet
Socket-Outlet Type	T2
Poles Description	3P + N
[Us] Rated Supply Voltage	380...415 V AC 50/60 Hz
Maximum Supply Current	32 A
Range Compatibility	EVlink EVlink parking EVF2 charging station EVlink EVlink parking EVW2 charging station EVlink EVlink parking EVP2 enclosure

Complementary

Material	Plastic
Height	260 mm
Width	110 mm
Depth	80 mm
Net Weight	1.34 kg
Colour	Green

Environment

Ip Degree Of Protection	IP54 conforming to IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ambient Air Temperature For Operation	-30...50 °C
Ambient Air Temperature For Storage	-40...80 °C
Relative Humidity	5...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	14.0 cm
Package 1 Length	28.0 cm
Package 1 Weight	1.583 kg
Unit Type Of Package 2	S03

Number Of Units In Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.58 kg

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
