


WHITE POINTER

8% COBALT



HEAVY DUTY stays sharper longer



Bi-Metal Holesaws

- Multiple ejection slots for rapid removal of thick and thin plugs (HSV40 and over)
- 4/6 variable tooth configuration reduces vibration for a smooth, accurate cut
- Unique multiple grinding technology for faster cutting and longer life
- Bi-Metal construction with 8% cobalt welded teeth for extended life in industrial applications
- International standard thread pattern accepts all common arbors

Holesaw sizes up to 38mm dia: 38mm cutting depth
Holesaw sizes 40mm dia and up: 48mm cutting depth

Ideal for: Steel, stainless steel, cast iron, non-ferrous metal, wood and plastic

Alpha CDT cutting fluid (code: ATL005) is recommended for increased life when drilling steel.

CARDED



CARDED - 1 PCE
Supplied in hangable or free-standing card

WHITE POINTER BI-METAL

WHITE POINTER BI-METAL				Suitable arbor					Suitable arbor
Ø mm	Ø inches	no. of ejection slots	CARDED 1 PCE		Ø mm	Ø inches	no. of ejection slots	CARDED 1 PCE	
14	9/16	1	HSV14	ARB-1 see page 131	65	2 9/16	3	HSV65	ARB-2 & ARB-3 see page 131
16	5/8	1	HSV16		67	2 5/8	3	HSV67	
17	11/16	1	HSV17		68	2 21/32	3	HSV68	
19	3/4	1	HSV19		70	2 3/4	3	HSV70	
20	25/32	1	HSV20		73	2 7/8	3	HSV73	
21	13/16	1	HSV21		75	2 15/16	3	HSV75	
22	7/8	1	HSV22		76	3	3	HSV76	
24	15/16	1	HSV24		79	3 1/8	3	HSV79	
25	1	2	HSV25		83	3 1/4	3	HSV83	
27	1 1/16	2	HSV27		86	3 3/8	3	HSV86	
29	1 1/8	2	HSV29		89	3 1/2	3	HSV89	
30	1 3/16	2	HSV30		92	3 5/8	3	HSV92	
32	1 1/4	2	HSV32		95	3 3/4	3	HSV95	
33	1 5/16	2	HSV33		98	3 7/8	3	HSV98	
35	1 3/8	2	HSV35	100	3 15/16	3	HSV100		
37	1 7/16	2	HSV37	102	4	3	HSV102		
38	1 1/2	2	HSV38	105	4 1/8	3	HSV105		
40	1 9/16	3	HSV40	108	4 1/4	3	HSV108		
41	1 5/8	3	HSV41	111	4 3/8	3	HSV111		
43	1 11/16	3	HSV43	114	4 1/2	3	HSV114		
44	1 3/4	3	HSV44	121	4 3/4	3	HSV121		
45	1 25/32	3	HSV45	127	5	3	HSV127		
46	1 13/16	3	HSV46	140	5 1/2	3	HSV140		
48	1 7/8	3	HSV48	146	5 3/4	3	HSV146		
50	1 31/32	3	HSV50	152	6	3	HSV152		
51	2	3	HSV51	160	6 5/16	3	HSV160		
52	2 1/16	3	HSV52	168	6 5/16	3	HSV168		
54	2 1/8	3	HSV54	177	7	3	HSV177		
55	2 5/32	3	HSV55	185	7 1/4	3	HSV185		
57	2 1/4	3	HSV57	200	7 7/8	3	HSV200		
59	2 5/16	3	HSV59	210	8 1/4	3	HSV210		
60	2 3/8	3	HSV60	250	9 13/16	3	HSV250		
64	2 1/2	3	HSV64						