



LED STRIPS FLP12V2M-6W/M

12V low voltage LED strip KIT 2m

Application

An creative solution for residential and commercial interior spaces

Design Specifications

- 12V weatherproof LED flexible strip with 3M self-adhesive tapes at back
- Pre-wired strip kit includes LED driver, LED strip & 1.2 m flex & 2 pin plug
- Plug & play ready to use
- High efficiency SMD LED chips, beam angle 115 degree, choice of 3000K or 5000K
- Stable working performance and even light output, heatsink recommended
- Cutable every 50 mm at the scissors symbol ✂, 2M and 5M kits optional. NOTE: when cutting LED strips, it is always important to calculate the remaining LED load to reconfirm its compatibility with the existing driver, as driver changes may be required with moderate reduction in loads.



IP44

ta25

TEXT PLUG

2 YEARS COMMERCIAL WARRANTY

3 YEARS RESIDENTIAL WARRANTY

DAYLIGHT 5000K

WARM WHITE 3000K

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Watts per metre (W/m)	Beam Angle (°)	Body Colour	CRI
FLP12V2M/WW/S	PRE-WIRED STRIP KIT IP44/20	240	6	115	CLEAR	80
FLP12V2M/NDL/S	PRE-WIRED STRIP KIT IP44/20	240	6	115	CLEAR	80

Model No.	Luminous Flux Per Meter (lm/m)	Dimensions (mm)	Colour Temperature (K)
FLP12V2M/WW/S	300	2000(L) x 8(W) x 2.5(H)	3000
FLP12V2M/NDL/S	300	2000(L) x 8(W) x 2.5(H)	5000

LED channel options: SLT1000, SLT3000, SLT3010, SLT3020, SLT3030, SLT3040, SLT3050, SLT4050, SLT5000

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

