





COOLUM PLUS S9068/TC - 9W

9 watt dimmable downlight, UGR<19, with flex and plug termination and selectable CCT

Application

Perfect for residential or commercial applications

Design Specifications

- 9 watt integral dimmable driver
- A versatile design supplied with flex and plug fitted for easy installation
- High efficiency LED optics with a multi-faceted reflector system
- CRI > 80, selectable CCT 3000 / 4000 / 5700K, beam distribution 60 degree, UGR<19
- Polyamide trim and body form in white or black
- IC 4 rated





















Performance

• Dimmable - YES

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	сст (к)	Beam Angle (°)
	S9068TC/WH	240	9	700/780/750	3000/4000/5700	60
	S9068TC/BK	240	9	570/630/610	3000/4000/5700	60

Dimmable	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	92	103	89(H)
YES	92	103	89(H)


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions

Dimensions





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

