

## Product data sheet Characteristics

# 755LPSMA4

Photoelectric Smoke Alarm FireTek - Wireless interconnect - Surface mount - 10-year lithium battery powered





Main	
Range	Fire Tek
Product brand	Clipsal
Product or component type	Smoke detector
Device application	Early detection of smouldering fires and open fires
Electronic sensor type	Photo-electric sensor

#### Complementary

Power supply type	Battery
Battery type	Lithium
Battery life	10 year(s)
Maximum rated operational current	70 mA
Control type	Button (test/hush function)
Maximum number of device interconnected	40 for wireless alarm
RF range	50 m indoor use line of sight 140 m in free field
Wireless response time	< 30 s
Transmission frequency	433420 kHz
Horn level	85 dB at 3 m, minimum
Time delay range	10 min (hush) 10 h (do not disturb)
Local signalling	Visual: 1 LED (red) for low battery indication Visual: 1 LED (red, green and blue) for wireless function status Sound: signal Sound: alarm
Type of installation	Indoor
Mounting support	Ceiling Wall
Diameter	130 mm
Depth	37.5 mm

#### **Environment**

Ambient air temperature for operation	045 °C
Relative humidity	595 %
Product certifications	RCM SAI Activfire
Standards	ISO 8201 AS 3786:2014

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	220.0 g	
Package 1 Height	13.5 cm	
Package 1 width	5.0 cm	
Package 1 Length	13.5 cm	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	

Life Is On